

XOANONS® Fluorine surfactant

Model number

XOANONS®WE-D8975BR

Incorporation

Could be added at any stage of the production process, including post addition.

Specification

Fluorocarbon copolymer solution
Transparent to slight yellowish clear
liquid
Dibasic ester
70%
$1.16\text{-}1.20$ g/ml $(25\pm1)^{\circ}$ C
30-80s(Tu-4 viscometer)(25±0.2)°C
>100℃

Note: This datasheet is intended to give typical results, not standard. Subject to COA.

Suggest addition

Addition to total formulation 0.05-0.8%

Storage stability

Keep intact 24 months in original package. Products beyond the storage period may continue to be used after inspection. The container must be closed immediately after use.

Application system

Solvent-based UV cure

Properties

- Good compatibility in varnish.
- Good long-wave leveling. Prevent orange peel phenomenon.
- Excellent ability of anti-cratering.
- Suitable for large area spraying, no foam-inhibition.
- After wet spraying and drying of multiple colors such as badminton rackets, the phenomenon of color channeling between colors can be prevented and eliminated.

Applicate recommendation

Transparency in varnish	4
Defoaming	2
Dynamic surface tension	4
Static surface tension	3.5
Slip	5
0=unavailable 5=very effective	

package

25KG / 180KG